




PanzerChain 2.4

for  VORON 2.4



Assembly Manual
Version 2020.09.08

Index

- Introduction
- What it is & what it is not!
- When to use?
- Improvements
- Printing
- Parts and Options
 - Links
 - Assembly of Links
 - X-Chain
 - Y-Chain
 - Z-Chain

Introduction

I find black chains boring and I couldn't find visually appealing printably chains that follow the spirit of Voron.

That's why I spent kilograms of filament and days of work to develop PanzerChain:

In 2019 the initial PanzerChain was born which was based on the well known igus design. This first release was liked by quite a lot people of the community due to it's design and functionality.

Even though this first iteration still works very well on my first Voron 2.2 i felt the need to improve it for 2.4 and my second Voron.

I am therefore particularly pleased to present PanzerChain 2.4

Enjoy!

What it is and what it is not!

- It is :
 - A custom energy chain for x/y and z axis meant to be used for Voron 2.4
- It is not:
 - An identical replacement for IGUS chain E2i.10.10.018 on XY-axis
 - ...nor for the E2.15.10.028 IGUS chain on Z-axis
 - A chain with separate compartments for wire organization
 - Perfect (for example it needs a little wear in time)
 - Compatible with any other chain

When to use?

- You like to print your own stuff :-)
- You like accessible/openable links for easy maintenance
- You prefer accent colors (see folder 'themes' for ideas)
- You want to save some money (it's not a lot! Go for Igus if in doubt or some alternative cheap Ali-stuff)
- You don't want to wait for your order to arrive
- You don't like tape chains (wire failure) or zip chains (fiddly)
- You don't care about
 - Extreme noise reduction
 - A not perfect bending radius
 - Or any other shortcomings due to additive manufacturing / fdm

Improvements of this Reboot


- Even easier to print
- Less supports
- More room where chain hits xy-joints
 - Probably some z-height loss
- Larger bending radius (ideal for heluflon wires)
- Clips are easier open without tools
- Removed unnecessary tolerance options
- New logo
- Nicer bending behavior (no s-curve/sagging but nearly pure u-curve)
- Revision Numbering from now on as VORON V2 (1 chain release per)

Printing

- do a test print of 3-4 xy-links
- check for layer adhesion
 - print slower and/or with higher temp if necessary
- filament: esun abs+
 - feel free to experiment, but don't blame me!
 - (petg seems to be okay or even superior based on user feedback)
- 0.2mm layer height incl. first layer
- no supports: required supports are already incorporated and easy to remove
- check your slicer preview: all walls need to be filled as much as possible
- tested at roughly 40mm/s - 60mm/s print speed (inner and outer shells)
 - if in doubt: go slower 25-30mm/s should work fine!
- at least 2 links per print for cooling time or slower speed
- Pressure Advance should be calibrated to allow for smoother kinematics (for example refer to [Klipper Documentation](#))

Assembly of Links

- 1) Open clips
- 2) Push inwards
- 3) Push out slightly outwards
(put a finger in the link)
- 4) Join





X-Chain

2x M3 heat inserts

x_anchor_direct_drive_x1.stl

xy_anchor_extrusion_x2

- 2x M3 Bottom Head ScREW
- Zip Ties




Y-Chain

xy_anchor_bridge_x1

1x M3 heat inserts

xy_bridge_x1.stl




xy_anchor_extrusion_x2

- 2x M3 Bottom Head ScREW
- Zip Ties

Z-Chain

z_anchor_gantry_x1.stl

- 2x M3x8 Bottom Head ScREW



z_anchor_frame_x1.stl

- 2x M3x8 Bottom Head ScREW

